

PRODUCT SPECIFICATIONS

EZ-Dry Systems



Model No:	EZD-E13	EZD-G13
Heat Source:	Electric	Gas or LPG
Evaporation Rate:	13 GPH	13 GPH
Energy Consumption:	34 kW/hour	205,000 BTU/hour
Gas Supply Pressure:	N/A	7" - 14" W.C.
Gas Inlet:	N/A	¾" NPT
Power Supply:	240V-3PH or 480V-3PH	120V-1PH
Full Load Amps (no fill pump):	86A (240V) or 43A (480V)	18.5A
Tank Capacity:	224 gal.	224 gal.
Operating Vol.:	112 gal.	112 gal.
Dimensions (L x W x H):	64" x 44" x 48"	64" x 44" x 48"
Shipping Dims. (L x W x H):	86" x 60" x 60"	86" x 60" x 60"
Empty Weight:	1,560 lbs	1,835 lbs
Approx. Ship Wt. Incl Thermal Oil:	2,770 lbs	3,245 lbs
Exhaust Stack:	10" OD	10" OD
Feed Water Inlet:	1" FNPT	1" FNPT
Thermal Oil Fill Inlet:	1" FNPT	1" FNPT
Thermal Oil Vent:	2" MNPT	2" MNPT
Thermal Oil Drain:	1" Valve	1" Valve
Materials:	Wetted components are 316L Stainless Steel. Exterior tank skins are 304SS.	

*Evaporation rate is based on tap water after reaching a boil. Evaporation rate may vary depending on altitude, ambient temperature and humidity, solids buildup on evaporator surfaces, boiling point elevation, exhaust stack configuration, off-spec power supply or gas pressure, characteristics of the wastewater, etc.